

charge. fast. anywhere.
Your mobile charging unit



NRGkick

Everything your EV ever needs for charging.

mobile charging unit for electric vehicles

Product data sheet



charge. fast. anywhere.
Your mobile charging unit



NRGkick

Safety connector system

For every electric vehicle (Type 2)

1-/2-/3-phases, up to 22 kW

Different cable lengths

5m, 7,5m or 10m

Light-weight and handy

Extra light for easy transport

Plug and Play

Intuitive operation, plug in and start charging

Intelligent

Access to all information with NRGkick App

Extremely robust

Drive-over proof, water-/dustproof (IP67)

Easy & fast

NRGkick charges all EVs with Type 2 interface at the maximum possible AC charging speed (up to 22 kW). It can be used immediately at any standard socket and, by means of the optionally available Type 2 smart attachment, also at public charging stations - without time-consuming installation.

Safe

NRGkick offers unprecedented safety features. The NRGkick's patented safety connector system, for example, ensures that dangerous arcing is eliminated and provides temperature monitoring for each smart attachment and on each individual phase pin - on both pins for domestic plug smart attachments.

Innovative

NRGkick is one of the most innovative charging units ever. Thanks to the full connectivity of the Internet of Things (4G M1, 4G NB-IoT, EDGE, GPRS), charging processes can be precisely assigned via GPS or WiFi location linking. Operation is convenient via the NRGkick app or with the swipe of a finger on the touch-sensitive surface of the charging unit.

Smart Attachment

32A 5Pole

3-phase | max. 22 kW



Smart Attachment

32A 3Pole

1-phase | max. 7,4 kW



Smart Attachment

16A 5Pole

3-phase | max. 11 kW



Smart Attachment

16A 3Pole

1-phase | max. 3,7 kW



Smart Attachment

Type 2

3-phase | max. 22 kW



Smart Attachment

domestic plug

1-phase | max. 13A
more variants available



Product information

Absolute safety

NRGkick is the safest charging unit on the market. It offers a wide range of safety features such as temperature monitoring at each smart attachment and phase pin, overheating protection, blackout protection and undervoltage protection, overvoltage protection, phase shift detection, false installation test, switching contact diagnosis, protective conductor test by means of loop impedance measurement, included residual current protection (AC, DC + 6 mA) and much, much more!

Full connectivity

Via Bluetooth, WiFi, NRGkick Cloud and the Web API, NRGkick is accessible always and everywhere. Optionally, the smart charging unit offers connectivity via GSM/GPS/SIM. The connection here is via EDGE, GPRS as well as 4G M1 and 4G NB-IoT and is thus equipped for the requirements of the Internet of Things.

Intelligent features

The variety of features makes NRGkick arguably the most intelligent charging unit on the market, which offers among others: Automatic charging reports, locally assignable charging reports via WiFi, display of charging costs, time-controlled charging, upgrade capability (e.g. photovoltaic-led charging), optional OCPP, grid-serving control option, autonomous load management, ...

Highest quality

NRGkick was the first mobile charging unit ever to be validated and certified by VDE and ÖVE. Not only NRGkick itself, but also the production meets the highest standards. Therefore, the manufacturing and production facility is continuously monitored and also certified by VDE and ÖVE.



Technical data

Type name

NRGkick

Nominal voltage

230V/400V 50Hz

Nominal current

32A

Maximum charging power

22 kW

RCD (AC)

30mA

RCD (DC)

6mA

IP protection class

IP67

Charge mode

Mode 2 according to IEC EN 62752

Mode 3 when using smart attachment Type 2

Weight

5m variant approx. 3,86 kg

CE compliance

CE compliant to **CE**
IEC EN 62752, IEC EN 62196,
IEC EN 60309

Operating conditions

-40°C.... +70°C (standard: +45°C)
5% - 95% humidity
max. 4.000m above sea level

Dimensions (L, W, H)

216mm x 90mm x 64mm

Connection technology

Bluetooth Low Energy (BLE),
WiFi; Optional: GSM- und
GNSS-interface (GSM: EDGE,
GPRS, 4G M1, 4G NB-IoT; GNSS:
GPS, GLONASS, Galileo, Baidou)

